



Balers
RV5100/5200 ^{PLUS}
Flexiwrap



vicon.eu



My way of Farming!

Kverneland Group - June 2020



My way of Farming!

PLUS Series

Variable Chamber Balers



The latest Vicon PLUS series RV balers combine profitable high output performance with market leading bale density. They benefit from a host of upgrades designed to boost output and reduce maintenance requirements, keeping operating costs to a minimum.

- Increased Feeding Capacity**
New roller crop press with increased lifting of the roller. Updated side support arms, new lower limit stops and fixed shafts with internal bearings providing improved protection.
- Enhanced Crop Flow**
New upgraded pick-up with longer pick-up tines and wider stripper plates for improved cleaning. Increased size and specification of pick-up drive chains with upgraded tensioners.
- Low Maintenance Driveline**
All bale chamber drives are equipped with heavy duty HBC specification chains, providing higher fatigue strength & increased wear resistance.
- Ultimate Reliability**
Rugged new Idler roller design with 45% increase in bearing diameter, larger internal grease capacity and improved shielding. A continuous central shaft also provides enhanced rigidity.
- Simplified Maintenance**
Bale chamber drive rollers with cast iron housings and centralised grease banks, ensure non-productive maintenance time is kept to a minimum.
- Enhanced Visibility**
New high level LED road light units mounted up out of harms way for reduced likelihood of damage from stray bales.
- Operator Convenience**
New improved foldable PTO stand also incorporates handy hose and cable storage. New easy access rear PTO cover for easier maintenance.



- 1. Superior Bale Quality**
Bale formation with five belts and three rollers provides dense, well shaped bales. Versatile multi-crop performance in silage, hay or straw.
- 2. Wide 2.2m low profile Pick-Up & High capacity intake systems**
Options of PowerFeed rotor intake or SuperCut 14 and 25 knife systems for accurate pre-chopping for optimal silage quality.
- 3. Parallelogram DropFloor**
Parallelogram drop floor system brings faster and easier clearing of blockages from the comfort of the tractor cab.
- 4. PowerBind Net Wrap**
PowerBind direct net injection for fast and highly reliable netting. Also featuring very low loading height for maximum convenience and time saving.
- 5. Intelligent Density 3D**
Fully programmable bale density setting with three pre-selectable options for silage hay and straw easily set from the control box.
- 6. Control System**
ISOBUS controls for easy and intuitive control and monitoring of main functions. All important settings are made from the comfort of the tractor cab.



Control Terminals:



Focus 3
NON ISOBUS
Simple and easy-to-use interface.



NEW Tellus GO **ISOBUS**
With a 7-inch touch screen allowing quick and easy machine set-up and control.



Tellus PRO - ISOBUS
Control the baler via the interface in the top screen.

The Variable Chamber Plus Series Baler Range



RV5100 PLUS



RV5200 PLUS



RV5200 PLUS FlexiWrap

Models	Bale dimensions (m)	Specifications
RV5116 Plus	1.20 x 0.80 – 1.65	Feeder Fork/DuoFeed/PowerFeed rotor/Net/Double
RV5118 Plus	1.20 x 0.80 – 1.75	Feeder Fork/DuoFeed/PowerFeed rotor/Net/Double
RV5216 Plus	1.20 x 0.60 – 1.65	PowerFeed rotor/SuperCut-14/SuperCut-25/Net/Double
RV5220 Plus	1.20 x 0.60 – 2.00	PowerFeed rotor/SuperCut-14/SuperCut-25/Net/Double
RV5216 Plus FlexiWrap	1.20 x 0.60 – 1.65	SuperCut-14/SuperCut-25/Net
RV5220 Plus FlexiWrap	1.20 x 0.60 – 2.00	SuperCut-14/SuperCut-25/Net

Information provided in this brochure is made for general information purposes only and for worldwide circulation. Inaccuracies, errors or omissions may occur and the information may thus not constitute basis for any legal claim against Kverneland Group. Availability of models, specifications and optional equipment may differ from country to country. Please consult your local dealer. Kverneland Group reserves the right at any time to make changes to the design or specifications shown or described, to add or remove features, without any notice or obligations. Safety devices may have been removed from the machines for illustration purposes only, in order to better present functions of the machines. To avoid risk of injury, safety devices must never be removed. If removal of safety devices is necessary, e.g. for maintenance purposes, please contact proper assistance or supervision of a technical assistant. © Kverneland Group Ravenna Srl