**Rotor Rakes**Single, Twin, Four





My way of Farming!





Working the land, running my farm and connecting with nature. Farming is my way of living, and despite being rough at times, I never grow weary of everyday tasks of attending to my land and livestock. I keep up with developments by staying loyal to personal philosophies and applying the appropriate strategy.

I shape and influence my own future by combining craftsmanship with modern technology, employing the very best machinery. I actively seek new opportunities, by being innovative in my way of working. I work hard to grow a good crop. I am passionate about my livestock, providing my animals with only the best. My farm and its returns, reflects who I am, because my heart and soul is put into the work I do.


Farming is about passion, about growing and developing, my crop, my farm, myself, my way.

## Durability

Steplessly adjustable cam track for easy adaptation to different amounts and types of crop.

Injection moulded aluminium tine arm support housings provide strength and reduced weight.

> Pinion gear with two bearings separate from the main driveline, keeping pinion and crown wheel securely in place.



All rotor star axles including housing can be removed individually by just removing 3 bolts.

400mm cast iron cam track with optimised shape, for smooth tine arm control and reduced running

arm shafts. Guide rollers with hardened surface minimise wear on cam

wear to a minimum.

Heavy duty ball bearings

excellent support of tine

with large distance for

Unique 4-point ball bearing on crown wheel ensures efficient power transfer to the tine arms



ProLine 10mm diameter tines.



Each tine arm can be dismounted and repaired individually.



The Andex ProLine rakes feature a unique drive system, which comprises an oil-immersed pinion and crown wheel. The fully enclosed design ensures full and permanent lubrication, and makes the entire system absolutely maintenance-free.

Our extensive experience guarantees well-proven technology of the highest standard. The hardened cam track is adjustable and with an extremely large 400mm diameter, giving precise guidance to the tine arms and quiet machine running.

The optimised shape of the cam track allows the tine arms to exit the crop faster, leaving a more uniform swath formation.

Aluminium bearing housings, with two widely spaced ball bearings, provide solid and maintenance-free tine arm mounting. Additionally all tine arms including the housing can be removed by simply removing 3 bolts. Fast and easy!

## Maintenance-Friendly

## Solution

#### CompactLine

The Andex CompactLine rakes feature oil-immersed cam track, guide rollers and tine bearings, eliminating maintenance on these components. Strong tine arms and bearings in an oilbath, ensure longevity and easy maintenance. The oil level of the gearbox is easily controlled from the outside.


High-tensile tine arm holders and two bearings on either side of the driveshaft provide the compact unit with strength and dependability. Vicondeveloped cam tracks are specifically manufactored for optimal raking at any working width and on any model.



crown wheel and Maintenance-free cam track and tine arms, running in an oil bath.

pinion.


High tensile tine arm holders for strength and dependability.



#### **Curved Tine Arms**

Correctly adjusting and customizing the rake to the exact conditions you are facing today is what adds the extra quality to your forage, ensuring that dirt stays out of the swath, yet leaving no crop behind. Setting the rotor height, adjusting the swath width and fine tuning the cam track (ProLine) is done easily and intuitively on all Andex rakes, taking the hassle out of the daily optimization.

The strong, yet flexible Vicon rake tines accurately move the crop into the swath, and with a wire diameter of up to 10mm they additionally provide the necessary capacity to move even large volumes of crop. The curved tine arms, a true Vicon hallmark, engineered to ensure that the tine arms will leave the swath at exactly the right time, promotes better and more accurate swath formation.





- · Higher lifting out of the swath
- · Increased capacity
- · Faster drying rates due to better formed, more fluffy swaths
- · Higher driving speed, as crop is pressed against the tines

#### **Curved Tine Arm Supports Regular and Even Swaths**

All Andex rakes are fitted with curved tine arms, to ensure a regular and even swath formation. Additionally the curved shape prevents material from being pushed along the tine inside the rotor to increase capacity.

The specially angled tine arms ensure a higher lift out of the swath and leave the swath at just the exact time in order to prepare regular and fluffy swaths.

## Stay on Track

## with TerraLink Quattro

What really matters is the quality of the silage and hay, which you produce. Precision in every part of the raking process is paramount to ensure that none of the valuable material is left behind, while at the same time securing a clean and attractive crop without dirt.

#### **Three-Dimensional Adaptation**

The TerraLink Quattro system has become a true legend related to accurate ground following, vital to avoid dirt in the swath - especially in uneven field conditions.

It is a rather simple, yet unique system providing excellent 3-dimensional adaption to ground contours. And it is absolutely maintenance- and wear-free.

#### The Strength is in the Arm

The openly constructed frame arm follows the principle of a torsion bar and absorbs vibrations away from the rotor and allows torsional flexibility, adding extra tracking flexibility and stability to the rotor. Each rotor operates in 3 dimensions to accurately respond and adjust to uneven field conditions.


#### **High Stability**

The trailed wheel axle configuration, where the weight is centered on the front bogie wheels, enhances quiet running and prevents lifting and tine bouncing. Each wheel is positioned as close as possible to the raking tines to ensure highest possible rotor stability, allowing higher travel speed.

#### How TerraLink Quattro Adapts in 3 Dimensions




The rotors are fully flexible in all directions, which means the tines have exceptional ground following ability....



... ensuring a clean raking result without dirt in the crop.





#### The Real TerraLink Quattro Advantage

The TerraLink system consists of two parts. First the lifting arm and second the undercarrier. The arm is slotted on the lower side. This, together with special steel quality, makes it possible for the frame to flex without breaking.






## Overview Rakes

## **ProLine**





#### Innovative Features on Range Models benefit your Grass Business



**Vicon Andex 1254 Plus** Hydraulic lowerable for transport below 4m.



**Vicon Andex 1505 Plus**Clever folding mechanism for road transport.

			0			
WORKING WIDTH	SWATH WIDTH	ROTOR DIAMETER	ROTORS	ARMS / ROTOR	TINE DIAMETER	CHASSIS / AXLE
9.80-15m	1.4-2.5m	3.85m	4 pcs.	13/15 pcs.	10mm	Cardanic
10-12.5m	1.2-2.2m	3.35/3.05m	4 pcs.	4x12/13 pcs.	10mm	TerraLink PLUS
10-12.5m	1.2-2.2m	3.35/3.05m	4 pcs.	4x12/13 pcs.	10mm	TerraLink Quattro
8-9m	1.4-2.4m	3.85m	2 pcs.	2x14 pcs.	10mm	TerraLink Quattro
7.60-8.40m	1.4-2.1m	3.65m	2 pcs.	2x12 pcs.	10mm	TerraLink Quattro
7-8m	1.2-2.2m	3.35m	2 pcs.	2x12 pcs.	10mm	TerraLink Quattro
7.7m	Variable	3.65m	2 pcs.	12/13 pcs.	10mm	TerraLink Quattro
4.6m	Variable	3.65m	1 pcs.	13 pcs.	10mm	Tandem
4.2m	Variable	3.35m	1 pcs.	12 pcs.	10mm	Tandem







Vicon Andex 1304 Plus ProLine adjustable cam.

## Overview Rakes

## CompactLine













CompactLine

ANDEX 1254 Plus	Multi-Rotor Center	
ANDEX 764	Multi-Rotor Center	
ANDEX 724 Hydro	Multi-Rotor Center	
ANDEX 724	Multi-Rotor Center	
ANDEX 644	Multi-Rotor Center	
ANDEX 644M	Multi-Rotor Center Mounted	
ANDEX 705 Vario	Multi-Rotor Side	
ANDEX 705 Evo	Multi-Rotor Side	
ANDEX 715T Vario	Multi-Rotor Side Trailed	
ANDEX 715T Evo	Multi-Rotor Side Trailed	
ANDEX 474T	Trailed	
ANDEX 424T	Trailed	
ANDEX 434	Mounted	
ANDEX 394	Mounted	
ANDEX 353	Mounted	
ANDEX 323	Mounted	

					/ <sup>   </sup>	
WORKING WIDTH	SWATH WIDTH	ROTOR DIAMETER	ROTORS	ARMS / ROTOR	TINE DIAMETER	CHASSIS / AXLE
10-12.5m	1.2-2m	3.05/3.35m	4 pcs.	4x12	9mm	TerraLink Quattro
7/7.80m	1.2-2m	3.35m	2 pcs.	11	9mm	TerraLink Quattro
6.2/7.2m	1.2-2.2m	3.00m	2 pcs.	11	9mm	TerraLink Quattro
6.2/7.2m	1.2-2.2m	3.00m	2 pcs.	11	9mm	TerraLink Quattro
6.4m	1.2m	3.00m	2 pcs.	10	9mm	Single
6.4m	1.2m	3.00m	2 pcs.	10	9mm	Single
6.65/7.85m	Min 1.0m, max depending on driver	3.35/3.23m	2 pcs.	11/12	9mm	TerraLink PLUS
6.65m	Min 1.0m, max depending on driver	3.35/3.23m	2 pcs.	11/12	9mm	TerraLink PLUS
6.6/7.1m	Min 1.0m, max depending on driver	2.95m	2 pcs.	11/12	9mm	TerraLink PLUS
6.6/7.1m	Min 1.0m, max depending on driver	2.95m	2 pcs.	11/12	9mm	TerraLink Quattro
4.2m	Min 1.0m, max depending on driver	3.65m	1 pcs.	12	9mm	Tandem
4.2m	Min 1.0m, max depending on driver	3.35m	1 pcs.	11	9mm	Tandem
4.2m	Min 1.0m, max depending on driver	3.35m	1 pcs.	12	9mm	Single
3.9m	Min 1.0m, max depending on driver	3.05m	1 pcs.	11	9mm	Single
3.5m	Min 1.0m, max depending on driver	2.8m	1 pcs.	10	9mm	Single
3.2m	Min 1.0m, max depending on driver	2.6m	1 pcs.	9	9mm	Single





#### ProLine



Andex 1505 Plus Working Width: 9.8-15.0m



Andex 1304 Plus / Andex 1304 Pro Plus Working Width: 10.0-12.5m

### CompactLine



**Andex 1254 Plus** Working Width: 10.0-12.5m



### Real 15m

## Working Width Machine

#### 15.00m Working Width

The Andex 1505 Plus is designed for high output and heavy use. Four rotors, maintenance-free ProLine gearbox, 15m working width and heavy duty mainframe design underline its potential as a rake for the most demanding customer segment.

## The Elbow Design Makes the Difference

The special elbow design of the front rotor arms is a unique feature of the Andex 1505 Plus. Raking width can be matched

to differing crop characteristics, to obtain an evenly shaped and equally wide swath across the full width.

The design also allows quick working width adjustment. In case of contact with an obstacle, the overload protection on the outer arm ensures that it folds back at a certain pressure, securing the main frame structure from damage.


Also when raking along borders, the fast moving front arms can

be used to steer along fences etc. without slowing down. Especially while raking corners, it is possible to clean them in one go as the front rotor can be pushed into the corner.

The biggest benefit of this system, is that the next swath will still be straight, as the rotor towards the non-raked area stays in position. When passing obstacles in the field, the front rotors can quickly be moved inwards, ensuring the swaths stay straight.



The unique elbow construction positions the front rotors close to the driver for excellent overview.





# Unbeaten *flexibility*

#### Tackle the Terrain

The front rotors are fitted with hydraulic ground pressure control for constant adjustment of ground pressure. Regardless of chosen working width, ground pressure remains even, allowing the rotor to instantly react to uneven field conditions for accurate tracking.

The advantages are obvious, as it leads to less damage and faster regrowth from the stubble and minimum dirt into the crop. Especially in wet conditions the low remaining weight on the rotor is a big advantage in order to get clean crop.

Adjustable hydraulic suspension on the front arms and fixed hydraulic suspension on the rear rotors takes the weight away from the undercarrier The hydraulics are operated on load sensing reducing fuel consumption, but also with possibility to run on constant flow.



All four rotors can be lifted individually.

#### A Superbly Manoeuvrable Unit

The 2-pt headstock allows a turning angle up to 80° and the optional unique steered wheel axles ensure these Vicon rakes have unequalled manoeuvrability. Despite a total length of 9.20m, even narrow gateways or approach lanes to fields are easily negotiated.

For easy headland management it is possible to tailor the sequence of lifting and lowering the front and rear rotors, to optimise the delay between front and rear rotors. Three different possibilities can be chosen. All 4 rotors can be lifted individually, allowing you to rake any size or shape of field in a professional and efficient way.



High lift of rotors ensures generous clearance during headland turns. Clearance height can be adjusted.



Each rotor can be independently and hydraulically set for height. A minimum height can be mechanically adjusted as well to secure correct setting.

#### **Brakes and Tyres**

The wide tires not only ensure gentle treatment of the ground, but also makes for excellent stability both in the field and on the road. Hydraulic or pneumatic brakes permit road speeds up to 40km/h.

All rotors are equipped with three pairs of wheels, which can rotate 360°, for perfect guidance and no danger of damage to the sward even when making the tightest turns.



## Customize the Size of Your Swath!

"Continuously
Adjustable
9.8-15.0m
Working Width"

#### **Adjustable Working Width**

Raking width can be continuously varied on the move between 9.80m and 15.00m. Raking width can be matched to the density of crop to obtain an evenly shaped and equally wide swath over the full length.

Working width can be adjusted, either during work or while stationary with rotors on the ground. If the width needs to be adjusted temporarily, the previously set working width can be recalled automatically.



The two outer rotors can be adjusted individually to obtain working widths between 9.8-15.0m.

## Everything Under Control with ISOBUS Technology

The Andex 1505 Plus is fully ISOBUS compatible. This means that it will be plug and play with an ISOBUS compatible tractor without the need for a separate terminal.

The Andex 1505 Plus is available with the IsoMatch Tellus 1200 or the IsoMatch Tellus 700 control terminals. The IsoMatch Tellus 700 is especially developed for controlling machines in a simple way. Just connect your machine, step into the tractor cab, switch on the power button and 700. The terminal brings the implement automatically into view. To maximise user comfort all but-tons are positioned on the right hand side of the terminal. No need to look at the touchscreen when operating the machine.

BreakBack system.



IsoMatch joystick.





#### **Take Full Control**

The following functions can be operated with the terminals:

- · Swath and working width.
- · Programmable lifting height of rotors.
- Automatic selection of transport or working position by pressing an icon.
- · Separate lifting of all four rotors.
- · Setting of rotor height.
- · Adjustment of working width, left and right hand side.
- $\cdot\,$  Active and selectable hydraulic suspension on front rotors.
- · Steering of transport axle.
- · Headland management activation.
- · Adjustment of delay time/meters or manual operation of headland managment.
- Special customised user interface, developed with contractors, for very simple control of functions.
- · Optional joystick.



The optional active wheel steering provides excellent manoeuvrability during narrow gateways and tight corners.



With its' clever folding mechanism the total height remains below 4.00m - despite a rotor diameter of 3.85m. And there is no need to remove tine arms for road transport.



## Keep Things **Simple**

#### **ProLine or CompactLine Specification**

The Andex 12.5m 4-rotor rake is offered with a choice of either ProLine or CompactLine gearbox. Both machines are similar in construction. They are built up on the same frame concept. The Andex 1254 Plus CompactLine version is an easy-to-use machine with substantial working width for the professional segment, looking for a dependable machine to ensure stability in the complete harvesting process.

For heavy duty conditions, the Andex 1304 Plus ProLine machine has been developed.

#### **Boost Your Work Day**

Andex 1254 Plus and 1304 Plus are targeted at making lighter work of tough and demanding operations. Being able to accurately feed the following machine and keep up efficiency of the complete harvesting system is an essential part of the raking job. With their impressive capacity of 12.50m working width, straightforward design and possibility to adjust both work and swath width from the cab, these machines are designed to boost the complete process of collection and pick-up, adjusting to the changing crop intensity during the season.



With 13 tine arms on the rear and faster front rotor securing superb capacity in heavy demanding crops.

## More Uptime with max 4m Transport

No reason for wasting time, not even when moving between fields. Just raise the rotors and off you go, safely below 4.00m transport height - no need to leave the tractor for removing tines arms. Large transport wheels and hydraulic brakes are standard.

For storage, all tines arms are detachable on Andex 1254 Plus to allow a storage height as low as 3.40m. A strong and stable storage foot ensures fast and trouble-free coupling and uncoupling.

For Andex 1304 Plus tine arms are generally fixed, but the top four are optional detachable, to reach same low storage height. A free wheel in the driveline ensures that these arms will always be facing upwards.

## Designed to Boost Capacity"

Easy and intuitive control function, all handled from the tractor cab.



#### Easy Handling - More Output

Andex 1254 Plus and 1304 Plus are designed with uncomplicated work days in mind. Forget about sophisticated sensors and control functions, they are designed around the operator with simplicity in mind, focusing on the elements that add real value. Take the control unit for instance.

It comes with a rather handy design including pre-selected functions for an array of easy operations. Only one double and one single acting spool valve are required to run Andex 1254 Plus and 1304 Plus.



TerraLink Quattro is a unique combination of flexible frame arm and 3-dimensional rotor suspension



## An Efficient

## Farming System



Working width can be set hydraulically between 10-12.5m. Swath width is also set hydraulically between 1.2 and 2.2m.

#### **Excellent Swath Formation**

To prevent an uneven appearance of the swath and to keep capacity up, the rear rotors\* are smaller in diameter and have one arm more. This secures the additional capacity needed on the rear rotors for the double volume, and as the rear rotor with one more arm, it also prevents roping\*.

The maintenance-free TerraLink Quattro rotor suspension system operates in three dimensions for excellent tracking, working in close combination with the four wheeled rotor to ensure high accuracy and stability on slopes. And it is absolutely maintenance- and wear-free.

<sup>\*</sup> Only for Andex 1304 Plus/1304 Pro Plus



1.2 - 2.2m Swath Width

## Hydraulic Adjustment of Working and Swath Width

The hydraulic adjustment of working and swath width allows you to customise swath intensity and width to the capacity of the following machine. All conveniently handled and controlled from the tractor seat. Working width can be set between 10-12.50m and swath width can be adjusted between 1.20-2.20m, adding the necessary flexibility.


#### **Easy Headland Management**

These machines come with enhanced headland management. In addition to high ground clearance of rotors during headland turns, it is possible to tailor time delay between lifting/lowering the front and rear rotors to driving speed and field conditions. This is done mechanically in an easy and uncomplicated way.

Andex 1254 Plus and 1304 Plus can make sharp turns of up to 80°, both on headlands and during transport when entering narrow gateways. The rotors can lift in pair as a standard feature, convenient for raking crop away from fence lines or when raking low crop fields. Optionally the front rotors can be lifted individually.







Compact but efficient machine - in combination with BX mower there is the possibility to collect up to 20m into one swath.



Optional tandem axle for additional stability especially on hillsides.



## Professional Handling

## - Maximized Productivity




#### Four rotor rake with ProLine Set-up

The Andex 1304 Pro Plus has an identical technical specification to the Standard Andex 1304 Plus. But with the "Pro" upgrade it features advanced operation possibilities thanks to ISOBUS control. With this add-on machine functions can be controlled easily from ISOBUS ready Terminal, for example Isomatch Tellus 1200 or Isomatch Tellus 700. And it provides further advanced possibilities to adjust and operate the machine.

#### Functions with ISOBUS:

- Folding and unfolding by just pressing one button
- Working width can be controlled from the terminal
- Possibility to save the swath width
- Different headland delay functions: Time/Distance/Manual delay



# "Individual lifting of all four rotors for efficient and clean raking"



With the individual lifting feature of all four rotors awkward shaped fields can be raked efficiently and cleanly.



With electric rotor height adjustment the min and max height is indicated as a percentage. It is possible to set your own zero point, to avoid accidentally raking lower than your field conditions allow. Lowering beyond this point will be shown on screen as a negative percentage.



Three optional work lights illuminate the critical area in front of the mainframe and one on the rear for swath and raking quality.



The high lift of the rotors ensures generous clearance during headland turns and allows sharp turns up to 80°







#### **ProLine**



Working Width: 7.0-9.0m



### CompactLine



Andex 644-644M-724 Hydro -764 Working Width: 6.4-7.8m



Andex 705 Evo/Vario Working Width: 6,65-7,85m Andex 715T Evo-715T Vario Working Width: 6.6-7.1m



## The Heavy Duty Centre Swath Rakes

#### **Durable Precision**

With adjustable working widths of 7.00m to 9.00m respectively these heavy duty specification rakes provide the swath formation capability to keep harvesting operations running at their optimal output. At the heart of all models is a heavy duty ProLine rotor head system. These models are equipped with ground protecting 380/55-17 tires.

#### On-the-Go Rotor Height Adjustment

A ComfortKit is optionally available for the Andex 804. This includes a handheld joystick control that brings all control functions into one. The height of each rotor is controlled electronically, and the actual height of each rotor is shown on the screen of the control box. In this way fine tuning rotor height, improving your work result is easily done on the go. A screen indicator shows the actual height in percent. It is also possible to set

a personal zero point, to prevent raking too deep. In addition the kit includes individual rotor lifting. It is possible to adjust the rotors together or individual in all positions.

#### Flexible Working Width

Andex 804:

7.00-8.00m working width.

Andex 844:

7.60-8.40m working width. Andex 904 Hydro:

Andex 504 Trydro.

8.00-9.00m working width.



#### **Excellent Manoeuvrability**

The rear carrier frame with controlled steering facility gives this rake excellent track following characteristics, allowing tight turns on headlands and loss free swathing even in awkwardly shaped fields. Even if the rotors are lifted on a steep slope, the steering system reliably counteracts any deviation. During headland turns the rotors are lifted up to 45cm from the ground to prevent swath damage.

- Actively steered wheels for excellent tracking.
- $\cdot\,$  Ability to make sharp turns up to  $80^{\circ}.$
- High lift of minimum 45cm of rotors ensures generous clearance during headlands turns.
- Single side lift: Raking with only one rotor (standard on Andex 904 Hydro, optional on Andex 804 and 844).





Andex 844 with 8.40m working width, fully enclosed gearbox and hydraulically adjustable working width.

Hydraulic adjustment of working width.









ComfortKit including electronic control of individual rotor height.



## More Uptime

## with Clever Transport Solutions

## Andex 804 - Design Optimised for Transport

The Andex 804 excels both with its extensive working width and compact transport dimensions. The new design of the wheel axles allows for the addition of generous 380/55 wheels as standard, whilst still offering a narrow outer track width, making it the perfect match for narrow roads and tight gateways.

Transport height is below 4.00m, even with all tine arms attached. No need to leave the tractor, just fold and go. Add in the 80° turning headstock and active wheel steering, and you have a highly manoeuvrable machine both on the road and in the field.



With 9.00m working width and transport height below 4.00m, even without detaching tine arms...



... the Andex 904 Hydro offers remarkable productivity with no downtime.

## Andex 904 Hydro - High Capacity in Field, Compact on the Road

The Andex 904 Hydro will go as wide as 9.00m during work with its twin rotors, and offers the flexibility to adjust the working width between 8-9.00m. It remains below 4.00m during transport, even with all tine arms fully mounted.

Thanks to the hydro axles, which are a unique Vicon feature, the complete rake can be lowered hydraulically for transport, ensuring that it will



go below 4.00m transport height. Another benefit is that the centre of gravity is lowered, and in combination with the wide track width and large 380/55-17 tyres it creates excellent weight distribution and stability during transport. Andex 904 Hydro comes as standard with a lift arm suspension and single side rotor lift.



The Andex 804 includes a transport height below 4.00m without leaving the tractor cab. Actively steered axles support tight turns on headlands and during transport.

Wheel arm is lowered hydraulically on Hydro models for reduced height in road transport. 380/55 flotation tyres are fitted for low ground pressure.



## Cost-Effective

## Centre Swath Rakes

Vicon offers five cost-effective double rotor rakes with strong design. The rakes produce a nice even centre swath with raking widths of between 6.20m and 7.80m. They are mounted on a strong and stable frame to ensure long lifetime. Features such as actively steered wheels, the TerraLink Quattro system and hydraulic working width adjustment are standard - except for the low cost entry level model Andex 644.



## Find your Step from Single to Twin Rotor System

When a single Rotor becomes too small and a twin rotor rake is the obvious next step, the Andex 644/644M is a fitting Entry Model to get more efficiency.

#### **Unique Manoeuvrability**

The rear carrier frame with controlled steering facility allows tight turns on headlands and loss free swathing even in awkwardly shaped fields. This gives ability to make sharp turns up to 80°.



Active wheel steering and sharp turns up to 80°.

# "Strong Frame Ensure Long Lifetime"



Height of the carrier frame offers outstanding ground clearance on headlands.



## Compact Design

## – High Performance



The hydraulically adjustable rotors can be set between 7.00m...



...and 7.80m working width on Andex 764.

#### Andex 724 and 764

Both Andex double rotor rakes offer hydraulically adjustable working width. This enables varying the swath width from 1.20-2.20m, ensuring a perfect match to the pick-up width of loader wagons, balers and foragers.

## Andex 724 Hydro - Resetting the Standard

The Andex 724 Hydro is fitted with hydraulically operated axles on the mainframe, in order to lift and lower the machine during transport and operation. This feature significantly reduces transport height by 40cm, allowing a transport height as low as 3.45m leaving all arms attached.



Lifting the machine.



Lowering the machine.



Add in features such as adjustable working width of 6.2-7.2m, TerraLink Quattro ground contour following and heavy duty carrier frame design, and the result is low maintenance, higher productivity and maximum operator comfort.

The CompactLine rotor gearbox, with all critical parts running in oil, helps to reduce maintenance time to a minimum.

All main functions, such as lifting and lowering of mainframe and rotors are operated from the tractor cab, using an electro hydraulic control terminal.

It is also possible to pre-select lift activation of the rotor units via the terminal. Such an integrated solution is offered only by Vicon.

# **" Higher Productivity**– MaximumOperator Comfort"



Vicon centre swath rakes are converted hydraulically for transport from the tractor cab.



To limit transport height further the tine arms can be removed on the Andex 764. The swath board folds up automatically.



The Andex multirotor rakes are fitted with TerraLink Quattro for excellent raking. (Except Andex 644)



## High Manoeuvrability

## for Narrow Roads and Awkward Fields




Compact transport position.

#### Andex 644M - Comfortable Dimensions

The CompactLine Andex 644M with its three point linkage mounting provides unrivaled maneuverability for accessing narrow roads and tight gateways. The mounting makes the Andex 644M therefore an ideal fit for mastering small and awkwardly shaped fields.

With its working width of 6.4m and 3.05m rotor diameter, it is suitable for raking 2x 3.2m mower swaths into one row.



## The Andex 644M is set-up with simple technology:

- · No ropes for transport locks.
- Only two positions, folded or unfolded (double acting cylinders).
- · No mistakes while operating.
- No need to operate with hydraulic valve during work.
- Easy headland lift with 3 point linkage.
- Outstanding clearance in headland position.
- Pivoting headstock to guide the machine freely along the field contour.
- · Fixed wheels can be used.
- Together with stabilizers, a perfect performance also on hillside is guaranteed.
- Optional tandem wheels can provide enhanced ground following.



Narrow and short transport position without leaving the cab.



More flexibility in storage as no tine arms need to be detached.



Better ground adaptation compared to larger single rotor rakes.



High flexibility on the road, and in the field, as no carrier frame is running on the crop.



Tandem axle (optional).



Height adjustment.



Vicon Andex 774.

## Double Up

## on Efficiency

The Andex 774 double rotor rake delivers a working width of 7.70m. The side delivery concept adds excellent flexibility in swath formation and allows you to collect crop from a working width of up to 15.00m into one swath. The high build mainframe concept offers excellent ground clearance in headland position. Actively steered wheels allow sharp turning, both on headlands and during transport.



A hydraulic foldable swathboard is optionally available for Andex 774.



Active wheel steering for improved manoeuvrability in combination with large wheels for reduced compaction.



The side delivery concept allows you to collect crop from 15.00m into a single swath.

# "Accurate Raking Performance"

#### **Exceptional Manoeuvrability**

Andex 774 is fitted with the renowned Vicon ProLine rotor gearbox, with its maintenance free oilbath solution. The shape of the Vicon hallmark, the massive 400mm cam track, allows the tine arms to leave the crop faster, leaving a more uniform swath shape.

In addition the rotors have been upgraded to 12 tine arms on the front rotor, each with 4 tines, and 13 tine arms, each with 5 tines on the rear rotor. This ensures more accurate raking performance, without roping, and allowing higher forward speed.

Vicon side delivery rakes have steerable undercarriers on the front rotor to secure smooth following in curves. In addition a swath board on the front rotor stops the crop, so it can be picked up by the rear rotor (Optional on Andex 705 Evo).

In addition Andex 774 is fitted with the Vicon TerraLink Quattro wheel system for superb ground contour following. This system controls the rotor in three dimensions.



Vicon Andex 705 Vario.

## Side Delivery Rakes

### - Proactive Performance



The Touch-Down-Effect, comparable to an aircraft's approach angle of its landing gear, ensures smooth and clean raking, but with lifting to a ground clearance of around 500mm avoids that swaths on headlands are damaged.


#### Andex 705 Side Delivery Rake

The Vicon Andex 705 Evo + Vario, a carried side delivery rake, delivers *flexibility* in raking, more *comfort* in operating and higher *quality* of forage due to the TerraLink Plus rotor attachment.

#### **Higher Quality of Forage**

With the updated feature "Terralink PLUS", rotor attachment benefits from a further advanced ground adaptation of 8°.

The Touch-Down effect in combination with Terralink Plus rotor mounting makes for smooth running and minimal soil inclusion in your forage, maximising forage quality, milk yields and animal health. In addition, 380mm guide wheels protect the sward from damage.





Vario two swathing.



Tandem wheels (optional).



Hydraulic transport locking (optional).

#### Flexibility in Raking:

- Unique rotor set up with a smaller rotor in the rear in combination with one more tine arm secures a perfect swath under all conditions
- · Improved steering geometry
- Steered tandem axles on the front and fixed on the rear ensure smooth running also in difficult conditions
- Perfect view towards left side of swath distribution
- · Automatic swath forming
- Vario enables to place two swaths, either for small balers in high crop volume or for night swaths to increase hay quality

#### More Comfort in Operation is delivered by:

- · Easy connecting of the machine
- · Automatic folding of the swath board
- · Optional hydraulic transport locking
- · Improved steering that gives you better maneuverability in the field
- Options like tandem axles support customizing the machine for individual requirements





Automatic fold-able swath board with parking stand.



Transport heigh below 4.0m.



Ground clearance >500mm.



## The Entrance to Flexibility and Capacity in Raking

#### Flexible Raking Performance

The Andex 715 T EVO is built for versatility in varying field conditions. Its twin rotors operate independently, allowing you to form either one large swath or two smaller ones. For high-volume raking, the rotors can combine two swaths into one — gathering up to 12.5 m of crop in a single pass. Features like QuickLift for easy headland turns, Swivel of the rear rotor, and the TerraLink system for smooth ground contour following make this rake a reliable and efficient choice.

#### **Compact and Clever Design**

The Andex 715 T EVO features a compact frame for excellent maneuverability and optimal rotor overlap. With no transport frame needed, the machine rides on its rotor wheels — ready for road travel fully mounted. The 50 cm headland lift clears large swaths with ease, and height adjustment is integrated into the lifting cylinders. The rear rotor's TerraLink frame connects at the ideal pivot point above the front rotor for smooth following and clean raking. Hydraulic swath board lift is rope-operated, and the advanced underlink connection with double wide-angle PTO ensures tight headland turns.

Optional extras include land wheels, tine savers, and a front swath board for placing two perfect individual swaths.



Two swath options flexible raking for efficient crop handling.



With 50cm lifting height, swaths can be driven over with no problem at all. Rotors are lifted using only a single acting valve.



Storage for the hydraulic lines.



Leaver to select swathplacement and activate stop in central position.

## Compact Transport & Smooth Travel

Simply swivel the rear rotor to the center — a built-in limiter helps guide it precisely, with a middle stop for easy alignment. Place the leaver in center position, the stop is deactivated, making it ideal for steering or storing the machine in tight spaces. On the road, the rake stays under 3 m wide fully mounted, and just 2.45 m width tine arms removed — perfect for shed storage.

The pulled undercarrier axle ensures smooth running and minimizes frame stress, even on rough roads.

#### **Consistent Raking Quality**

Raking performance is central to the design. With 11 tine arms in front and 12 in the rear, the machine offers high capacity and forms a uniform swath — ensuring clean pickup and topquality forage at the right time.





Lot of options are available to customise the machine.



Pulled axles ensure smooth handling and low frame stress on both road and field.



## Premium Raking **Solution**

## Smart Design for Clean Fields and Happy Cows

The Andex 715T Vario builds on the proven EVO concept with smart upgrades: 11 tine arms in front and 12 in the rear ensure perfect swath shape. The hydraulic swiveling of the rear rotor allows flexible swath formation — single or double. Tandem wheels on both rotors provide smooth ground tracking, and the 50cm headland lift keeps swaths undisturbed. Premium features like the unique front rotor SideShift

and TerraLink Plus flotation system deliver precision in tough terrain. All functions are controlled from the cab via the pre-selection box — no ropes. Designed to make your work easier — and your cows happier.

#### Vicon SideShift – Clean Raking, Less Crop Damage

The Vario version offers the SideShift system as standard, which comprises electro-hydraulic control of all functions. SideShift offers the possibility to shift the front rotor in addition to the rear. It lets the rotor run right of the tractor, ideal for raking near trees or wet spots without driving too close. This reduce damages on the tractor especially in soft soil — helping to minimize ash contamination and crop loss. Another unique possibility thanks to the SideShift is to reduce the driving on top of the crop shifting the front rotor to the left. Specially with soft soil this is reducing Ash contamination and crop loss a lot.

#### **TerraLink Plus Flotation System**

In addition to the standard TerraLink system, the Vario model feature the TerraLink Plus flotation system, offering an extra 8° of movement on the rear rotor. This enhanced flexibility ensures perfect ground tracking, especially in short, uneven field sections. Combined with the compact machine design, it delivers superior cleaning and minimizes crop loss. For added convenience, rear rotor height adjustment is easily accessible from the top - simple, comfortable, and efficient.



The 715T Vario with 7.10m working width in double swath position.



SideShift to the right - easy cleaning of borders with perfect view on the rotor



SideShift to the left - raking without driving on the crop.



TerraLink Plus ensures smooth rotor movement and precise ground tracking for optimal raking.

#### **High end Features**

The vario as the Evo is standard equipped with tandem wheels on both rotors. In addition the machine comes standard with the land wheel on the drawbar supporting a perfect ground tracing in SideShift positions. The rear rotor is on top equipped with inner land wheels, securing a perfect tracking of the ground. All this allow the Andex 715T Vario to operate in all type of field. It is the only rake supporting you to reduce driving on the crop. We understand how to create high quality forage.



made for tough terrain"



Easy adjustment of rotor height in the back.



Full control from the cab - no ropes, just smart raking.





#### ProLine



**Andex 424-464**Working Width: 4.2-4.6m

### CompactLine



**Andex 323-353-394-434** Working Width: 3.2-4.3m



Andex 424T-474T Working Width: 4.2-4.7m



## Built-In *Reliability*



Tine arms can be easily removed.

#### **High Performance**

Vicon ProLine single rotor rakes feature a gearbox design with excellent performance. Features such as oscillation dampers, tandem axles and HydroLift height adjustment are standard hallmarks of ProLine single rotor rakes.

#### **HydroLift Concept**

A unique Vicon feature of the Andex 424 and 464 is the standard HydroLift concept. It is a hydraulic height adjustment system that allows the driver to quickly adjust working height to different ground conditions from the tractor cab as well including the possibility to mechanically set a minimum height.



For transport or storage, the rotor guard frames are folded up close to the mainframe, locking automatically into position. An assistor spring linked to the swath board reduces the effort required.

#### **ProLine Gearbox**

Andex single rotor rakes are based on the ProLine gearbox technology. These machines have working widths of 4.20m and 4.60m respectively and are fitted with the renowned Vicon ProLine gearbox, with its maintenance-free oilbath solution.

The shape of the Vicon hallmark, the massive 400mm cam track, has been improved to allow the tine arms to leave the crop faster, leaving a more uniform swath shape.

Both rakes are fitted as standard with both four wheel tandem axles and oscillation dampers, offering excellent ground contour following, minimising the amount of dirt collected in the swath.




Oscillation dampers ensure excellent running characteristics.



As an option these rakes can be supplied with a third wheel, to ensure even better flotation.



Infinitely variable cam track adjustment allows fine tuning, to obtain optimal raking and swath formation according to crop conditions.




HydroLift height adjustment also offers the possibility to set a minimum height.



## Compact Design

### - Low Maintenance



Compact design for easy maintenance.

#### The Compact Range

For smaller raking operations, Vicon offers several models designed for use on lower horsepower tractors, whilst delivering similar raking performance compared to its higher specification machines. With the pivoting three point linkage machines and also trailed versions, there is a model to suit any need, from lowland farmers, to users working on steep hillsides.

#### Andex 'Compact' Rotor Head

The rotor head is grease lubricated. Within a fully enclosed housing, the maintenance-free cam track and cam followers are running permanently lubricated in an oilbath. The rotor shaft and pinion shaft are all mounted on two bearings for maximum strength and long service life.



The Andex 394 with 3.90m working width for fast and effective raking action. Also perfect for turning straw swaths.

#### **Curved Tine Arms**

All Andex CompactLine rakes feature cranked tine arms for significantly cleaner raking performance and optimised swath formation. This design ensures that the row of tines on each tine bar has a more effective approach angle to the oncoming crop, and also gives a cleaner lift out of the tine from the formed swath.







The Andex 353 with 3.50m working width offers high performance with a simple, but reliable system.



All rakes can be set for reduced transport and storage width by removing the tine arms and placing them on the carrier frame.



A pivoting 3-pt headstock ensures perfect ground following performance, and perfect tracking when cornering. Oscillation dampers are optionally available.



Andex 474T – 4.70m working width and a weight of only 665kg.



With a linkage mounted drawbar, the Andex 474T and 424T can be easily operated by low horse power tractors.





The machine can conveniently be raised up to a height of 50cm from the tractor driver's seat.



## Original Parts & Service

## We are here so you can focus on your crop





With MYVICON you will benefit from easy access to Vicon's online service tools. Receive first hand access to information on future developments and updates, operator and spare part manuals, FAQs and local VIP offers. All information is gathered in one place.

REGISTER YOUR PRODUCT NOW: MY.VICON.EU

## Facts

	Single Rotor Rakes									Double Rotor Rakes			
Model Andex	323	353	394	424	424T	434	464	474T	644	644 M	705 Vario		
Dimensions & Weights		,											
Working width (m)	3.20	3.50	3.90	4.20	4.20	4.30	4.60	4.70	6.40	6.40	6,65/ 7,85		
Working width (ft)	(10'6")	(11'6")	(12'10")	(13'9")	(13'9")	(14'1")	(15'1")	(15'5")	(20'10")	(20'10")	(21'8"/		
Transport width (m)	1.60	1.75	1.75	1.75	2.00	2.10	2.15	2.40	2.80	2.85	25'8") 2.80		
Transport width (ft)	(5'3")	(5'8")	(5'8")	(5'8")	(6'6")	(6'9")	(7'1")	(7'9")	(9'2")	(9'3")	(9'2")		
Transport length (m)	3.10	3.35	3.60	3.15	3.90	3.85	3.35	4.80	5.90	3.85	8.65		
Transport length (ft)	(10'2")	(10'12")	(11'10")	(10'4")	(12'10")	(12'7")	(11')	(15'9")	(19'4")	(12'6")	(28'4")		
Parking height (m)	1.60	1.70	1.85	2.60	2.30	2.00	2.75	2.65	3.85	3.81	3.99		
Parking height (ft)	(5'3")	(5'6")	(6'1")	(8'6")	(7'6")	(6'6")	(9'0")	(8'7")	(12'7")	(12'5")	(11'5"/ 13'1")		
Weight (kg)	315	420	460	640	570	480	670	665	1510	1200	2240		
Weight (Ib)	(694)	(926)	(1014)	(1410)	(1256)	(1058)	(1477)	(1466)	(3329)	(2646)	(4938)		
Swath width (m)	-	-	-	-	-	-	-	-	1.20	1.20	-		
Swath width (ft)	-	-	-	-	-	-	-	-	(3'11")	(3'11")	-		
Capacity theo. (ha/h)	3.5	3.9	4.3	4.6	4.6	4.7	5.1	5.2	6.9	6.9	7.6/8.7		
Hitching system													
Pivoting 3-pt headstock (cat.)	1/2	1/2	1/2	2	-	1/2	2	-	-	-	-		
Lower links (2-pt.)	-	-	-	-	-	-	-	-	•	•	•		
Linkage drawbar	-	-	-	-	•	-	-	•	-	-	-		
Gauge wheel 16°	0	0	0	0	0	0	0	0	-	-	_		
Rotors/Tine arms/Tines											2.25/		
Rotor diameter (m)	2.60	2.80	3.05	3.35	3.35	3.35	3.65	3.65	3.00	3.05	3.35/ 3.23		
Rotor diameter (ft)	(8'6")	(9'2")	(10')	(11')	(11')	(11')	(12')	(12')	(9'9")	(10')	(11')		
Swath delivery	left	left	left	left	left	left	left	left	centre	centre	left		
Number of rotors	1	1	1	1	1	1	1	1	2	2	2		
Number of arms per rotor Number of double tines/	9	10	11	12	11	12	13	12	10	10	11/12		
arm	3	4	4	4	4	4	4	4	4	4	4		
Tine diameter (mm)	9	9	9	10	9	9	10	9	9	9	9		
Adjustable cam track	-	-	-	•	-	-	•	-	-	-	-		
Detachable tine arms/rotor	•	•	•	•	•	•	•	•	-	-	•		
Height adjustment	rack trail	mech.	mech.	hydr.	mech.	mech.	hydr.	mech.	mech.	mech.	mech.		
Wheels and axles													
Tyre (rotors)	15x 6.00-6	16x 6.50-6	16x 6.50-6	16x 6.50-6	18x 8.50-8	16x 6.50-6	16x 6.50-6	18x 8.50-8	16x 6.50-6	16x 6.50-6	16x 6.50-6		
Fixed tandem axle	0	0.50-6	0.50-6	0.50-6	8.50-8	0.50-6	0.50-6	8.50-8	0.50-6	0.50-6	-		
Pivoting tandem axle	-	-	-	0	-	-	0	-	-	-	-		
Stand. tyres (carrying frame)	-	-	-	-	-	-	-	-	10.0/ 75-15.3	-	380/ 55-17		
Opt. tyres (carrying frame)	-	-	-	-	-	-	-	-	-	-	-		
Optional Equipment													
Hill side stabiliser	0	0	0	•	-	0	•	-	-	-	-		
Lift arm suspension	-	-	-	-	-	-	-	-	-	-			
Safety accessories													
Warning panels	0	0	0	0	•	0	0	•	•	•	•		
Road lights	0	0	0	0		0	0						

Information provided in this brochure is made for general information purposes only and for worldwide circulation. Inaccuracies, errors or omissions may occur and the information may thus not constitute basis for any legal claim against Kverneland Group. Availability of models, specifications and optional equipment may differ from country to country. Please consult your local dealer. Kverneland Group reserves the right at any time to make changes to the design or specifications shown or described, to add or remove features, without any notice or obligations.

										Four Rotor Rakes			
705 Evo	715T Evo	715T Vario	724	724 Hydro	764	774	804	844	904 Hydro	1254 Plus	1304 Plus	1304 Pro Plus	1505 Plus
	6.60/	6.60/	6.20/	6.20-	7.00/	-	7.00-	7.60-	8.00-	10.00-	10.00-	10.00-	9.80-
6,65	7.10*	7.10* (21'8"/	7.20	7.20	7.80	7.70	8.00 (23'-	8.40 (24'11"-	9.00	12.50	12.50	12.50	15.00 (32'2"-
(21'8")	(21'8"/	(21'8"/	(20'4"/ 23'7")	(20'4"/ 23'7")	(23'/ 25'7")	(25'3")	(23'- 26'30")	(24'11"- 27'7")	(26'3"- 29'6")	(32'10"- 41')	(32'10"- 41')	(32'10"- 41')	(32'2"- 49'3")
2.80	23.4") 2.20**/	23.4") 2.20**/	2.80	2.80	2.80	2.85	2.80	2.98	2.98	2.99	2.99	2.99	2.99
	3.00	3.00 (7'3"**/											
(9'2")	9'10")	9'10")	(9'2")	(9'2")	(9'2")	(9'3")	(9'2")	(9'8")	(9'8")	(9'8")	(9'8")	(9'8")	(9'8")
8.65	7.40**/ 8.20	7.40**/ 8.20	5.90	5.90	5.90	8.90	5.95	6.25	6.25	8.75	8.75	8.75	9.85
(28'4")	(24'3"**/ 26'11")	(24'3"**/ 26'11")	(19'4")	(19'4")	(19'4")	(29'2")	(19'52")	(20'6")	(20'6")	(28'8")	(28'8")	(28'8")	(32'4")
3.5**/	- 2011)	- 2011)	3.85	3.45***/	3.45**/	3.70**/	3.41/	3.45**/	3.50**/	3.45/	3.45/	3.45/	3.45**/
3.99 (11.5"/				3.95 (11'3"/	4.10	4.10 (10'6"/	3.90 (11'2"/	4.10 (11'3"/	3.98	3.99 (11'3"/	3.99 (11'3"/	3.99 (11'3"/	4.00 (11'3"/
13'1")	-	-	(12'7")	13")	13'5")	13'5")	12'10")	13'5")	13'1")	13'1")	13'1")	13'1")	13'1")
2300	1520	1600	1640	1680	1640	2160	2065	2285	2350	4300	4700	4700	6000
(5071)	(3351)	(3527)	(3615) 1.20-	(3704) 1.20-	(3615) 1.30-	(4762)	(4553) 1.20-	(5038) 1.40-	(5181) 1.40-	(9480) 1.20-	(10362) 1.20-	(10362) 1.20-	(13228) 1.40-
-	-	-	2.20	1.90	1.90	-	2.20	2.10	2.40	2.20			
-	-	-	(3'11"-	(3'11"-	(4'3"-	-	(3'11"-	(4'7"-	(4'7"-	(3'11"-	(3'11"-	(3'11"-	2.50 (4'7"-
7.6	7.3	7.3	7'3") 7.5	6'3") 7.5	6'3") 8.4	8.5	<u>7'3")</u> 8.8	<u>6'11")</u> 9.2	7'10") 9.9	<u>7'3")</u> 13.8	7'3") 13.8	7'3") 13.8	8'2") 16.5
1.0				1.5		0.5	- 0.0	7.2		13.0	13.0	13.0	10.0
=	-	-	-	-	-	-	-	-	-	-	-	-	-
•	-	-	•	•	•	•	•	•	•	•	•	•	•
-	•	•	-	-	-	-	-	-	-	-	-	-	-
-	0	•	-	-	-	-	-	-	-	-	-	-	-
3.35/ 3.23	2.95	2.95	3.00	3.00	3.35	3.65	3.35	3.65	3.85	3.05/ 3.35	3.05/ 3.35	3.05/ 3.35	3.85
(11')	(9'6")	(9'6")	(9'10")	(9'10")	(11')	(11'12')	(11')	(12')	(12'7")	(10'/11')	(10'/11')	(10'/11')	(12'7")
left	left	left	centre	centre	centre	left	centre	centre	centre	centre	centre	centre	centre
2	2	2	2	2	2	2	2	2	2	4	4	4	4
11/12	11/12	11/12	11	11	11	12/13	2x12	2x12	2x14	4x12	4x12	4x12	13/15
4	4	4	4	4	4	4/5	4	4	4	4	4	4	4/5
9	9	9	9	9	9	10	10	10	10	9	10	10	10
-	-	-	-	-	-	•	•	•	•	-	•	•	•
•	•	•	-	-	•	•	(4)	•	(4)	•	• (4)	● (4) mech./	-
mech.	mech.	mech.	mech.	mech.	mech.	mech.	mech./ opt.	mech.	mech./ opt.	mech.	mech.	opt.	hydr.
							hydr.		hydr			hydr.	
16x	18.5x	18.5x	16x	16x	16x	16x	16x	16x	16x	16x	16x	16x	16x
	8.50-8	8.50-8	6.50-6	6.50-6	6.50-6	6.50-6	6.50-6	6.50-6	6.50-6	6.50-6	6.50-6	6.50-6	6.50-6
6.50-6	0.30-0						0	0	0	0	0	0	Terra
6.50-6	0.30-8	•	0	0	0	-	0						
-			0	-	-	-	-	-	-	-	-	-	Contact
-	•	•	0							500/ 50-17	500/ 50-17	- 500/ 50-17	
380/	•	•	0 - 10.0/	10.0/	10.0/	380/	380/	380/	380/	500/ 50-17 710/35	500/ 50-17 710/35	500/ 50-17 710/35	Contact 560/
- - 380/ 55-17	- -	-	0 - 10.0/ 75-15.3	- 10.0/ 75-15.3	10.0/ 75-15.3	380/ 55-17	380/ 55-17	380/ 55-17	380/	500/ 50-17	500/ 50-17	- 500/ 50-17	Contact 560/
- - 380/ 55-17	- -	-	0 - 10.0/ 75-15.3	- 10.0/ 75-15.3	10.0/ 75-15.3	380/ 55-17	380/ 55-17	380/ 55-17	380/	500/ 50-17 710/35	500/ 50-17 710/35	500/ 50-17 710/35	Contact 560/
- - 380/ 55-17 -	-	-	0 - 10.0/ 75-15.3 -	- 10.0/ 75-15.3	- 10.0/ 75-15.3	- 380/ 55-17 -	- 380/ 55-17 -	- 380/ 55-17 -	- 380/ 55-17 -	500/ 50-17 710/35 R22.5	500/ 50-17 710/35 R22.5	500/ 50-17 710/35 R22.5	Contact 560/ 60-22.5
- 380/ 55-17 - -		-	0 - 10.0/ 75-15.3 - -	- 10.0/ 75-15.3 - -	- 10.0/ 75-15.3 -	380/ 55-17 -	- 380/ 55-17 -	- 380/ 55-17 - 0	- 380/ 55-17 -	500/ 50-17 710/35 R22.5	500/ 50-17 710/35 R22.5	500/ 50-17 710/35 R22.5	Contact 560/ 60-22.5
- 380/ 55-17 -	-	- -	0 - 10.0/ 75-15.3 -	- 10.0/ 75-15.3 -	- 10.0/ 75-15.3 -	380/ 55-17 -	380/ 55-17 -	- 380/ 55-17 -	- 380/ 55-17 -	500/ 50-17 710/35 R22.5	500/ 50-17 710/35 R22.5	500/ 50-17 710/35 R22.5	Contact 560/ 60-22.5

Safety devices may have been removed from the machines for illustration purposes only, in order to better present functions of the machines. To avoid risk of injury, safety devices must never be removed. If removal of safety devices is necessary, e.g. for maintenance purposes, please contact proper assistance or supervision of a technical assistant. © = trade mark protection in the EU. © Kverneland Group Kerteminde AS

