

**Rotary Tedders**  
4 - 14 rotors



# Fanex Rotary Tedders



*My way of Farming!*







# KEEP YOUR PRODUCTIVITY RUNNING

*My way of Farming!*



Working the land, running my farm and connecting with nature. Farming is my way of living, and despite being rough at times, I never grow weary of everyday tasks of attending to my land and livestock. I keep up with developments by staying loyal to personal philosophies and applying the appropriate strategy.

I shape and influence my own future by combining craftsmanship with modern technology, employing the very best machinery. I actively seek new opportunities, by being innovative in my way of working. I work hard to grow a good crop. I am passionate about my livestock, providing my animals with only the best. My farm and its returns, reflects who I am, because my heart and soul is put into the work I do.

Farming is about passion, about growing and developing, my crop, my farm, myself, **my way.**



# CompactLine *Models*

## *Mounted Tedders*



### ***Vicon Fanex 464-524***

Compact tedders with low maintenance.  
Working width of 4.6-5.2m.



### ***Vicon Fanex 604-804***

Compact tedders - ideal for hay making.  
Working width of 6.05-8.05m.



# ProLine *Models*

## *3-Point Mounted Tedders*



### ***Fanex 554-684-764-904-1124***

New Generation of heavy duty mounted tedders - strong driveline - compact transport dimensions. Working width of 5.5, 6.8, 7.6, 9.0 and 11.2m.

## *Semi-Mounted Tedders*



### ***Vicon Fanex 904C-1124C***

Mounted tedders with transport running gear. Working width of 9m.

## *Carrier Frame Tedders*




### ***Vicon Fanex 1344C-1564C***

Carrier frame tedders. Working width of 13.4 and 15.6m.



## CompactLine - *Maintenance-Friendly Gearbox*



“**Easy**  
and efficient  
Set-up”



“**Gearbox**  
– is not a  
part of the  
mainframe”



# ProLine

## - Maintenance-Free Gearbox



**“No maintenance of the gearbox required – permanent oilbath lubrication”**

### A Strong Reliable Heart

Vicon ProLine tedders feature a uniquely designed self-contained rotor gearbox. The ProLine gearbox requires no maintenance, and is situated in an enclosed oilbath, set up to ensure permanent lubrication. No service or maintenance of the ProLine gearbox is needed.

The gearboxes do not serve as part of the frame, but are bolted onto the fully welded mainframe. This ensures that no load and strain from frame will be transmitted by the gearbox, adding to significantly longer lifetime.

The ProLine gearboxes feature reliable crown and pinion drives positioned in one housing. The main crown wheel in each gearbox is mounted directly to the casing by means of double bearing. The double bearings on both sides of the hexagonal drive shaft keeps the shaft securely in place, even when operating in heavy duty wet crop.



The large drive shafts and double U-joints give smooth, efficient transfer of power through the frame allowing each rotor to accurately follow field contours.

### Heavy Duty Mainframe Design

The Vicon tedders are built around a rugged new box section mainframe, made out of one piece of metal with only one welding seam – for maximum rigidity. The frame design is fully enclosed at the top edge for maximum strength – an exceptionally solid design, which allows the Vicon tedders to withstand the most severe loads.



Maintenance-free roller bearing for best possible performance and higher second hand value.

\*only ProLine



## ProLine Super-C Tines – Even Spread, *Clean Job*



Super-C tine with symmetric spring tines ensure efficient pick-up and turning of the crop. Tines with same lengths has the added advantage that load is spread evenly on both tines, providing longer lifetime.\*

Made from flat steel, the tine arms form a very compact unit with the rotor plate and utilize the force of the rotor plate for higher durability of the tine arm. This makes a Fanex tine arm by far more resistant to any type of load.

The Super-C tine can be locked in three positions to customize the pick-up angle to different conditions. For heavy silages the angle can be set more aggressive and for fragile crop a more gentle angle can be chosen.

Made from 10mm shot-peened spring steel and a coil diameter of 80mm, Super-C tines add up to the most durable and flexible tine in the market.\*

**“An airy  
and evenly  
spread crop  
speeding up the  
drying process”**

### Take the Lead in Beating the Weather

Vicon tedders help you produce high quality crop, even under difficult weather circumstances. Ever changing weather conditions often leave a very tight time window to prepare the crop. When the weather proves to be flexible, it is about vital machines which are ready to operate as flexible as needed.

The Vicon tedders are the right tool to accomplish uniform and rapid drying action of the crop. The Vicon Super-C tines, working with generous overlap thanks to the rotor design:

- equal length tines
- consistent burden
- longer service life
- easier warehousing
- direct initiation of turning operation



Optional third wheel lead to even more accurate track following and better tedding action.

\*Compact line standard C-tines with coil 68 mm and 9 mm tines.



### The Super-C Tine

In order to produce high quality silage or hay, the crop must be spread evenly across the field to facilitate a uniform drying process. In addition soil contamination is a no go. The symmetric Vicon Super-C tines of identical length efficiently pick up the crop and start turning of the crop already during the pickup process for fast effective wilting. The crop is spread evenly and thrown over a wide distance.

Tines with same lengths has the added advantage that load is spread evenly on both tines, providing longer lifetime.

The Vicon Super-C tines are made of 10mm shot-peened spring steel. Spring diameter coils have 20% larger diameters than conventional designs for added service life, even when tedding large quantities of crop.



Generous overlap ensures that crop is spread evenly.




Left: Super C-Tine 10mm  
Right: Standard C-Tine 9mm

“**20% larger spring diameter** than conventional designs”



Easy adjustment of spreading angle via pin holes, no tools required.



### Setting the Right Spreading Angle

Simple three-way adjustment of wheel height, allows the optimum spreading angle to be achieved according to crop conditions, helping you to produce high quality forage.

Setting the rotors to the right spreading angle will improve considerably the spreading action and speed up the drying process. Set a steep angle for aggressive conditioning effect or choose the more flat angle for more gentle treatment of dry or very fragile material.

# Oscillation Dampers *for Smooth and Even Crop Distribution*



## **Oscillation Dampers**

The Vicon oscillation dampers ensure excellent ground contour following and tedder flotation. The construction of the oscillation dampers results in a smooth and even distribution of the grass, due to the constant tine distance to the ground. The distant linkage point means that it offers excellent running characteristics compared to conventional oscillation dampers.


The fact that the linkage is positioned low on the headstock results in a more effective damping action during transport.






“**Smooth and even distribution** of the grass”

- Widely spaced mounting points  
- no risk of 'hunting'
- Excellent running characteristics
- Low-positioned linkage on the headstock for more effective damping action during transport
- No risk of the tedder mounting up driving downhill, excellent tedding at all times through constant time spacing to the ground
- Maximum stability in transport position - no further lock of headstock required.



Conventional systems



Vicon oscillation dampers

# FANEX PROLINE ROTOR TEDDERS

*My way of Farming!*





### *ProLine*



**Fanex 1344C-1564C**  
Working Width: 13.4 - 15.6m



**Fanex 904C-1124C**  
Working Width: 9.0 - 11.2m



**Fanex 554-684-764-904-1124**  
Working Width: 5.5 - 11.2m





## Serious Fun – Large Working Width, *Simple Operation*

### **Real Working Power**

Fanex 1344C and 1564C offer greater productivity in all crop types. With working widths of 13.4m and 15.6m it is designed with high output and excellent crop quality in mind. All elements are dimensioned for intensive use, focusing on providing optimum productivity and reduced downtime, with very low maintenance level for easy, enjoyable operation.

Featuring 12 or 14 small diameter rotors, these tedders are designed for excellent crop turning in almost any conditions. The small diameter rotor design provides a generous overlap between the rotors, giving an efficient pick-up and turning of the crop as well as equal distribution over the complete working width.

### **Minimum Maintenance**


The operator of these tedders will enjoy their easy maintenance specifications with long service intervals. Greasing points are limited to a minimum and driveline (except the PTO), rotors and most of the joints are maintenance-free.





Fanex 1344C and 1564C are easily unfolded in three steps. First it is lifted with the single acting valve out of the transport brackets. Secondly it is unfolded into headland position via the double acting outlet. Lastly it is lowered by putting the single acting valve into free float position.

**“New innovative**  
ground following  
system with a highly  
flexible frame”





## Excellent Ground *Tracking*

### **TerraFlow**

Accurate ground following is paramount to achieve an excellent feed result. Especially in challenging and demanding field conditions. You want to efficiently turn the crop, not the soil. The Vicon solution to outstanding ground following is the TerraFlow solution.

This innovative ground following system provides a highly adaptive frame connection allowing each of the rotors to accurately follow ground contours. With its new solution for connecting tedder unit and carrier frame the rotors are able to flex and adapt to ground contours.

The tedder unit follows the chassis wheels and adapts completely independent of the movement of the carrier frame. This means tine distance to ground remains constant in all terrain, providing clean and accurate work and a uniform crop flow. A unique Vicon feature that brings ground adaptation and forage quality to a new level.





Both models fold into a transport width below 3m and its driven like a trailer on road smoothly following behind the tractor.

### Easy Operation

All it requires to operate is a single acting valve ram for raising and lowering the tedder and a double action valve ram for the folding action, so this tedder is suited for most tractors.

Activating the headland position to pass areas already spread could not be easier. You just need to activate the single acting valve to lift the tedder unit, giving generous clearance, maneuverability and driving stability.

With the border spreading device you keep the crop inside the field when tedding along borderlines on headlands. The optional hydraulically activated swath board efficiently keeps crop within the working width of the tedder.



Hydraulic height adjustment is optionally available and controlled with an additional double acting valve. The scale is easily read from the cabin, making it simple to set the machine correctly.



Fitted with generous 380/55-17 tires giving stability and good ground protection. 500/50-17 tyres are available as option.



A hydraulic swath board ensures that crop stays within working width of the machine (option).



High clearance in headland position.





## Productivity *at the Core*



Strong and sturdy mainframe design with V-shaped central unit.



New aluminium rail guards, which are low in weight, but still extremely impact resistant.

### **Maintenance Made Easy**

Powered by maintenance-free driveline and gearboxes, focus can be directed towards the essentials to maximize productivity. No time is wasted on time consuming greasing. Additionally the hinges are connected with strong maintenance-free roller bearings for extended longevity and stability of the connection points.





All tedders can be equipped with a third wheel to ensure correct set-up of the tedder independent of tractor and driver.

### Heavy Duty Confidence

Vicon's new generation of mounted tedders is designed to perform perfect in all crop conditions, with a minimum of non-productive maintenance required and with diminished transport dimensions. Fanex 554 provides a working range of 5.5m, the 6-rotor Fanex 684 and 764 offer 6.8 and 7.6m working width, while the 8-rotor Fanex 904 spans 9.0m.

Featuring a heavy duty fully closed headstock and a strong V-shaped central unit, these machines will fit perfectly into the operation of professional farmers, looking for a strong, effective, and versatile tedder.

### High Quality Tedding In all Conditions

- maintenance-free
- reduced efforts in season
- high loads transferring
- heaviest crop
- strong oscillation dampers
- even spreading pattern
- easy standard settings

**“Perfect for all crop conditions**  
– strong,  
effective and  
versatile!”





## Reduced Transport Height – *Increased Efficiency*



To increase productivity these tedders are equipped with the mechanical border tedding device. Optional a hydraulic solution is available. A marker cleverly shows the position of the axle.



**“Compact in transport**  
– new clever folding mechanism”



Compact in transport and during storage thanks to the new clever folding mechanism.



Fanex 684 in transport.

**“180° folding**  
for transport”

#### Compact Transport Dimensions

These ProLine tedders offer very compact transport dimensions with their new clever folding solution. A reduced parking height is possible, due to the implementation of the HexaLink finger clutch system in the joints of the two outer rotors (Fanex 764 and 904). The remaining rotors are driven by double acting foldable cylinders\*. They provide safe unfolding under all conditions.

\*Except 554



Vicon HexaLink finger clutch permits a 180° folding of the rotors for transport. (Fanex 764, 904 and 1124 (C)).



A hydraulic headland kit is optionally available.\*



## Accurate Tedding *at High Capacity*



Fanex 1124 is fitted with the XL version of HexaLink finger clutch.

### **11m High Capacity Tedder**

From heavy duty silage to hay making, the Fanex 1124 is designed to provide an excellent spreading job, significantly speeding up the drying process. Delivering 11.2m working width from 10 rotors, each fitted with 6 tine arms per rotor, the result is high performance and output.

Fanex 1124 is fitted with the new XL version of HexaLink finger clutch providing reliable power transfers and 180° folding of the rotors for transport.

Featuring a heavy duty fully closed headstock, the Fanex 1124 fits perfectly into the operation of professional farmers, looking for a strong, productive and versatile tedder.



**Advantages:**

- 10 rotor system
- small diameters
- optimal usage of working width
- no cable control for unlocking
- biggest 3-point tedder with 11.2m

**“New folding mechanism**  
– even weight distribution”



Compact transport dimensions of Fanex 1124  
– storage height is only 3.80m.



With the optional electro-hydraulic headland kit with pilotbox, the machine can be raised while on headlands using the hydraulic control device.

**Easy to Work With**

The largest in the Vicon range of mounted rotary tedders comes with a folding mechanism, providing extra stability when folding on hilly terrain. This ensures even weight distribution during the complete folding sequence. Thanks to the new HexaLink finger clutch system, the Fanex 1124 folds into very compact transport and storage dimensions. Despite its impressive working width of 11.2m, this rotary tedder offers storage height as low as 3.85m and a transport width of only 2.95m.



**New folding mechanism** – ensures even weight distribution during the complete folding sequence.



## Designed for Compact Tractors *Starting From 60hp*



### **Clever Transport Solution**

The new Fanex 904C is a 9m, 8-rotor and the 1124C with 11.2m and 10 rotors carrier frame tedder purpose-built for use with smaller tractors. The wide track width ensures stable running characteristics during road transport. Due to the carrier frame concept, the lifting capacity of the tractor is not a limiting factor and it can be operated with tractors starting from 60hp.

In road transport, tedder weight rests on the running gear, rather than on the tractor's rear axle. The optimised driveline provides low input requirement, so you can easily use a small tractor and still work at wide working widths - the ideal solution that saves fuel and running costs.






Tandem axle (option).



Get the most out of your crop. With border tending you keep the crop inside the field. The tedder is swung hydraulically into border position, conveniently tending the crop away from the border line.



New optional third wheel with tandem axle for high accuracy in ground followings.







## Reliable Performance *with Smart Transport Solution*

### **The Carrier Frame Takes the Strain**

The carrier frame concept of a Fanex 904C and 1124C allows to be managed with smaller tractors than conventional sizes. These two models offer very compact storage and transport height due to the implementation of the HexaLink finger clutch system in the joints of the two outer rotors.

Vicon Fanex 904C = 3.74m  
Vicon Fanex 1124C = 3.94m

The remaining rotors are driven by maintenance-free universal joints, for strong and efficient transfer of power, including the possibility of running in folded position.





**“Hydraulically  
converting  
from transport  
to working  
position”**



Standard running wheels of Fanex 904C are extra wide 10.0/75 – 15.3 tyres with a generous track width of 2.45m.



**From transport to working position:**

Fanex 904C easily converts from transport to working position and fold hydraulically.



# FANEX COMPACTLINE ROTOR TEDDERS

*My way of Farming!*







### *CompactLine*



**Fanex 604-804**  
Working Width: 6.05-8.05m



**Fanex 464-524**  
Working Width: 4.6-5.2m





## The Hay Making ***Tedders***

Fanex 604 folds hydraulically from working to transport position and vice versa.







The strong design of the V-shaped central unit provides high stability during tedding operation and allows high transport speed.




Standard oscillation dampers ensure an even spreading pattern.

### Powerful Dimensions

Fanex 604 and Fanex 804 come with a strong package of Vicon features, such as 2 oscillation dampers, strong V-shaped central unit and central adjustment for border tedding.

They offer considerable working width with their combination of 6/8 rotors and 6.05m/8.05m working width.

The very small rotors are especially designed for optimized performance while producing dry hay, but will fit any kind of crop. The compact rotors, in combination with a big overlap, ensure complete pick-up of the grass and equal distribution over the entire working width.





## Achieve More ***with Fanex 804!***

### **Compact Folding for Transport**

Despite its 8.05m working width the Fanex 804 will fold into a very compact unit for transport, and will go below 3.00m transport width. The two outer rotors are fitted with the new Vicon HexaLink finger clutch, a simple yet efficient drive system. The remaining rotors are driven by double universals joint, providing sturdy and efficient transfer of power.




### Built to Last – Minimum Maintenance

The Fanex 804's superior durability and ease of maintenance ensure maximum machine uptime. It is designed with a strong package of Vicon features such as 2 oscillation dampers and strong V-shaped central frame unit for stable and accurate running characteristics.

The rotor gearbox is designed to just keep going and only requires greasing once per season of just one point. Additionally the unfolding process is done via double acting cylinders, for troublefree operation under all conditions.



Fanex 804 folds into a very compact position for transport.



Compact dimensions during storage.



Vicon HexaLink finger clutch permits the rotors to fold 180° for transport.

**“Compact dimensions during storage”**



Easy adjustment of spreading angle.



With the optional reduction gearbox it is possible to place night swaths.



Hydraulic border tedding (option).



## Compact – *Easy to Maintain*

### **Low Maintenance**

With working widths of 4.60m and 5.20m, Vicon offers the CompactLine range with low maintenance rotor gearboxes. The rotors of the Fanex 464 and 524 are driven by a low maintenance gearbox with only one grease nipple.

The double bearings from pinion to crown wheel guarantee maximum longevity of the driveline. The low weight of these models is ideal for application with small tractors, or in hilly regions.






All tedders fold hydraulically from working to transport position and vice versa.

### Incredible Dimensions

Even the smallest models excel – the rotor plate diameter measures 500mm! All Fanex tedders feature gearboxes flanged to the frame, and which have no supporting function, and are therefore not subjected to any strain.

This system sets the benchmark with respect to stability, smooth running, quality of work and efficiency. Compare for yourself.

All models are fitted with a central adjustment device for setting the machine at the correct angle for border tedding. This is set mechanically from the tractor cab and is done in very few seconds. Optionally hydraulic operation is available too.







## Powerful ***Dimensions***



Keep the crop inside the field with border tedding.



As an option the tedders can be equipped with a third wheel to improve contour followings.



Standard oscillation dampers ensure an even spreading pattern.





Optional reduction gearbox makes night swath tedding possible.

**“Centrally  
adjustment  
for border  
tedding”**




Fanex 464 and Fanex 524 are centrally adjusted for border tedding.

## Original Parts & Service

***We are here so you can focus on your crop***

- 
- ① Long lasting, high quality spare parts
  - ② Over 100 years of parts knowledge
  - ③ Support from a wide network of dealers
  - ④ 24/7 spare parts service
  - ⑤ Highly skilled dealer technicians





**“MYVICON**  
Connected farming, my way”

#### **A personalised online platform tailored to your machine needs**

With MYVICON you will benefit from easy access to Vicon's online service tools. Receive first hand access to information on future developments and updates, operator and spare part manuals, FAQs and local VIP offers. All information is gathered in one place.



**REGISTER YOUR PRODUCT NOW:  
MY.VICON.EU**

# Facts

Model Fanex	CompactLine			
	464	524	604	804
<b>Dimensions &amp; Weights</b>				
Working width* (m)	4.60	5.20	6.05	8.05
Working width* (feet)	(15'1")	(17'1")	(19'10")	(26'5")
Width, working position (m)	5.00	5.40	6.40	8.35
Width, working position (feet)	(16'5")	(17'9")	(20'12")	(27'5")
Transport width (m)	2.85	2.90	2.75	2.90
Transport width (feet)	(9'4")	(9'6")	(9')	(9'6")
Transport length (m)	2.15	2.10	1.86	1.90
Transport length (feet)	(7'6")	(6'11")	(6'17")	(6'23")
Storage height (m)	2.45	2.65	3.10	3.15
Storage height (feet)	(8')	(8'8")	(10'2")	(10'33")
Weight approx. (kg)	500	530	650	920
Weight approx. (lbs)	1102	1168	1433	2028
Capacity theor. (ha/h)	3.7	4.2	4.8	6.4
<b>Attachment</b>				
Three-point, tracking	1/2	1/2	1/2	2
Linkage drawbar	-	-	-	-
Two-point, linkage arms	-	-	-	-
Oscillation damper/integral lock	●	●	●	●
<b>Rotors/Tines/Guard</b>				
No. of rotors	4	4	6	8
No. of tine arms / rotor	5	6	5	5
Tine adjustment system	●	●	●	●
Adjustment of spreading angle	●	●	●	●
Cab contr. border clearing system, Mechanical	●	●	●	●
Cab contr. border clearing system, Hydraulic	0	0	0	0
Reduc. gearbox for night swaths	0	0	0	0
<b>Tyres/Axles/Lights</b>				
Wheels	16x6.5-8	16x6.5-8	16x6.5-8	16x6.5-8
Tyres on central unit	-	-	-	-
Front wheel (16x6.50-8)	0	0	0	0
Tandem axles	-	-	-	-
Warning panels	0	0	0	0
Warning panels, with integr. lighting	0	0	0	0

● Standard   0 Optional   - Not available   \* DIN 11220   \*\* Height with hydraulic swath board   \*\*\* 40/50mm tow. eye - 80mm hitch ball cpl







ProLine								
554	684	764	904	904C	1124	1124C	1344C	1564C
5.50 (18'1")	6.80 (22'4")	7.60 (24'11")	9.00 (29'6")	9.00 (29'6")	11.20 (38'8")	11.20 (38'8")	13.40 (44')	15.60 (51'2")
5.80 (19')	7.15 (23'5")	7.90 (25'11")	9.45 (31')	9.45 (31')	11.70 (38'35")	11.70 (38'35")	13.92 (45'9")	16.17 (53'1")
2.98 (9'9")	2.92 (9'7")	2.96 (9'9")	2.94 (9'8")	2.94 (9'8")	2.94 (9'65")	2.96 (9'71")	2.99 (9'10")	2.99 (9'10")
2.30 (7'7")	2.20 (7'3")	2.26 (7'5")	2.16 (7'1")	4.21 (14')	2.16 (7'7")	4.26 (13'9")	6.77 (22'3")	6.77 (22'3")
2.80 (9'2")	3.52 (11'7")	3.46 (11'4")	3.49 (11'5")	3.74 (12'3")	3.80 (12'43")	3.94 (12'93")	2.89/3.20** (9'6"/10'6"*)	2.89/3.20** (9'6"/10'6"*)
640	900	990	1260	1700	1600	2225	3195	3410
1410	1984	2183	2778	3747	3527	4905	7044	7518
4.4	5.4	6.1	7.2	7.2	9.0	9.0	10.8	12.5
2	2	2	2	-	2	-	-	-
-	-	-	-	-	-	-	●	●
-	-	-	-	2	-	2	-	-
●	●	●	●	-	●	●	-	-
4	6	6	8	8	10	10	12	14
7	6	7	6	6	6	6	6	6
●	●	●	●	●	●	●	0	0
●	●	●	●	●	●	●	●	●
●	●	●	●	-	●	-	-	-
0	0	0	0	●	0	●	0	0
0	0	0	0	0	0	0	0	-
16x6.5-8	16x6.5-8	16x6.5-8	16x6.5-8	16x6.5-8	16x6.5-8	16x6.5-8	16x6.5-8	16x6.5-8
-	-	-	18.5x8.5-8	18.5x8.5-8	18.5x8.5-8	18.5x8.5-8	16x6.5-8	16x6.5-8
0	0	0	0	0	0	0	-	-
0	0	0	0	-	0	0	-	-
0	0	0	●	●	●	●	●	●
0	0	0	●	●	●	●	●	●





Safety devices may have been removed from the machines for illustration purposes only, in order to better present functions of the machines. To avoid risk of injury, safety devices must never be removed. If removal of safety devices is necessary, e.g. for maintenance purposes, please contact proper assistance or supervision of a technical assistant. ® = trade mark protection in the EU. © Kverneland Group Kerteminde AS

# Facts

## The Right Tedder for Every Cutting Width

































































ProLine	 ROTORS	 ROTOR WIDTH	 ROTOR TINES	 WORKING WIDTH
FANEX 1564C	14	1560mm	6	15.60m
FANEX 1344C	12	1560mm	6	13.40m
FANEX 1124/1124C	10	1560mm	6	11.20m
FANEX 904/904C	8	1560mm	6	9.00m
FANEX 764	6	1660mm	7	7.60m
FANEX 684	6	1560mm	6	6.80m
FANEX 554	4	1760 mm	7	5.50m

CompactLine	 ROTORS	 ROTOR WIDTH	 ROTOR TINES	 WORKING WIDTH
FANEX 804	8	1420mm	5	8.05m
FANEX 604	6	1420mm	5	6.05m
FANEX 524	4	1660mm	6	5.20m
FANEX 464	4	1560mm	5	4.60m





























WORKING WIDTH\* / SWATHES\*\*

1.6m 2.0m 2.4m 2.8m 3.2m 3.5-3.6m 4.0m 8.7m 9.0m 9.5m 10.2m

WORKING WIDTH\* / SWATHES\*\*


1.6m 2.0m 2.4m 2.8m 3.2m 3.5-3.6m 4.0m 8.7m 9.0m 9.5m 10.2m

\*only full working width covering pictured

\*\*based on average swath width

# Proud History of Ground Breaking Innovations



*My way of Farming!*



[www.vicon.eu](http://www.vicon.eu)