

**EXTRA**  
787-795



## Triple Mower Conditioners



*My way of Farming!*

# Versatile 8.75 & 9.50m Triple *Mower Conditioners*

## High Performance Mowing

The EXTRA 787 & 795 series is based on the 700 series platform and includes well-established features like QuattroLink suspension concept, SemiSwing steel tine or rubber roller conditioning and dual adjustment of conditioner plate.

These mower conditioner models are developed for maximum productivity and offer excellent ground tracking, easy operation and outstanding versatility.

Comprising two 3.2 or 3.5m mowing units, each with 8 or 10 counter-rotating triangular discs, this combination can be operated by tractors starting from 180hp.

EXTRA 787 and 795 models are easy to handle and standard operated with a pre-selection joystick for (individual) lifting/lowering of mowing units and belts and setting of ground pressure.



### 1. QuattroLink® Racecar Suspension

Innovative suspension concept for accurate tracking. The 4-arm suspension provides the mowing unit with an exceptional flexibility in adapting to demanding ground contours.

### 2. Full Width BreakAway

When encountering an obstacle in the field the mowing unit will swing backwards and over the obstacle, even on the inside of the mower, and then return it to the original mowing position.

“*Medium Segment Machine*  
With High End  
Suspension”



**3. Intensive Conditioning**

The conditioner plate can be adjusted at both front and rear ends to customize the conditioner to crop intensity. Use the two handles to set the desired conditioning intensity.

**4. Vertical Transport Position**

Vertical transport position, with a 50/50% weight balance, allows a higher transport speed. With the integrated vertical parking foot limited storage space is required.

**5. BX Belt Solution**

Both 787T and 795T are available in BX versions with belt merger for efficient crop collection. The BX versions offer significant possibilities to improve productivity and quality of output. The swath belts are designed for work with massive volumes of crop, including heavy first cut silage.



The machine folds into a an above 90° transport position, keeping the mowing units away from treetops.



Vicon EXTRA 787 and 795 series can be combined with either a 3.2 or 3.6m front.



Vicon EXTRA 787T QuattroLink triple mower combination with 8.75m working width.



All hydraulic functions are controlled via the tractor valves in combination with a pre-selection PilotBox.

Facts

Model EXTRA	Triple Mower Conditioners				
	787T	787R	787T BX	795T	795T BX
Dimensions & Operation					
Working width (m)	8.75	8.75	8.75	9.50	9.50
Conditioner	SemiSwing	Roller	SemiSwing	SemiSwing	SemiSwing
Weight appr. (kg)	3015	3075	3575	3300	3775
Number of triangular discs	2x8	2x8	2x8	2x10	2x10
PTO power req. min (kW/hp)	130/180	130/180	155/210	155/210	175/240

Information provided in this brochure is made for general information purposes only and for worldwide circulation. Inaccuracies, errors or omissions may occur and the information may thus not constitute basis for any legal claim against Kverneland Group. Availability of models, specifications and optional equipment may differ from country to country. Please consult your local dealer. Kverneland Group reserves the right at any time to make changes to the design or specifications shown or described, to add or remove features, without any notice or obligations. Safety devices may have been removed from the machines for illustration purposes only, in order to better present functions of the machines. To avoid risk of injury, safety devices must never be removed. If removal of safety devices is necessary, e.g. for maintenance purposes, please contact proper assistance or supervision of a technical assistant. © Kverneland Group Kerteminde A/S



[vicon.eu](http://vicon.eu)



*My way of Farming!*